



## ProLine™ Series Hose Data Sheet

### Application:

A lightweight and very flexible with high durability water hose for a wide range of uses listed as:

- Residential Landscapes
- Light Commercial

**Value:** Medium-duty, ensure long-life. Lightweight and very flexible w/ low drag resistance.



**Working Pressure:** 125 Psi @ 70 F (34.47 bars @ 21.1 C)

**Burst Pressure:** 500 Psi @ 70 degrees F (8.62 bars @ 21.1 C)

**Tube:** Black, TPE material, RMA Class B (Medium Oil Resistance)

**Cover:** Matte tan, TPE material, RMA Class B (Medium Oil Resistance)

**Reinforcement:** Spiral synthetic yarn

**Temperature Range:** -10°F to 158°F (-23°C to 70°C)

**Hose Diameters:** (Imperial and metric values)

	5/8"	3/4"
<b>ID:</b>	0.614 to 0.646" (15.6 to 16.4 mm)	0.780 to 0.811" (19.8 to 20.6 mm)
<b>OD:</b>	0.783 – 0.831" (19.9 to 21.1 mm)	0.953 to 1.00" (24.2 to 25.4 mm)

**Weight/ft.** (imperial and metric values)

5/8"	3/4"
0.115 lbs. max (0.052 kg)	0.145 lbs. max (0.066 kg)

**Weights:** (Imperial and Metric Values)

Size	Hose Lengths (Imperial and Metric weights)		
	50' (15.24m)	75' (22.86m)	100' (30.48m)
5/8"	6.50 lbs. (2.72 kg)	9.50 lbs. (4.08 kg)	12.5 lbs. (5.44 kg)
3/4"	7.5 lbs. (3.40 kg)	11.5 lbs. (5.22 kg)	15.5 lbs. (7.03 kg)

**Available Lengths:** 50', 75' & 100', (custom lengths upon request)

**Ordering Information:**

5/8" Hose Diameters		
Model No.	Length Ft. (m)	Description
H58-050PRO-G	50' (15.24m)	5/8" ProLine Hose Gold 50' length
H58-075PRO-G	75' (22.86m)	5/8" ProLine Hose Gold 75' length
H58-100PRO-G	100' (30.48m)	5/8" ProLine Hose Gold 100' length
3/4" Hose Diameters		
H75-050PRO-G	50' (15.24m)	3/4" ProLine Hose Gold 50' length
H75-075PRO-G	75' (22.86m)	3/4" ProLine Hose Gold 75' length
H75-100PRO-G	100' (30.48m)	3/4" ProLine Hose Gold 100' length

**Couplings:** Machined brass, FHT or MHT

5/8": Male and female garden hose fittings (5/8" - 11 1/2" NH threads) & 0.900" ID ferrules

3/4": Male and female garden hose fittings (3/4" - 11 1/2" NH threads) & 1.025" ID ferrules

**Origin of Manufacturer:** United States

**Branding / Identification on Layline of Hose:**