


# Underhill® FUSION™

**2Wire Decoder-in-Solenoid**

*Advanced Technology*



**Now for the first time.....**

**2Wire Decoder built-into a valve solenoid**

## **Special Features**

- ✓ Combines a 2Wire Decoder and Solenoid into one product
- ✓ Reduces number of field wire connections by 50%
- ✓ Multi-colored LED provides feedback – reduces troubleshooting time
- ✓ Fits most valves w/ threaded adapter
- ✓ Compatible w/ all Underhill 2Wire Controllers or 2Wire Converters
- ✓ Superior distance and simultaneous valve operation
- ✓ Built-in powerful lightning surge protection

**Once in a while, a product comes along that changes everything....**

# Electrical Specifications

- 19-32 VAC 60 Hz
- In-Rush Current – 300-350mA
- Holding Current-30mA (2-way solenoid) 60mA (3-way solenoid)
- Idle Current – 4.5mA
- Maximum Number of Simultaneous Valve Operation
  - 2-way 16 (spread relatively equally along the 2Wire path)
  - 3-Way 10 (spread relatively equally along the 2Wire path)
- Maximum Operating Distance (single valve actuation)\*
  - 10 AWG – 71,500Ft.
  - 12 AWG – 35,750 Ft.
  - 14 AWG – 32,500 Ft.

\* the more simultaneous operating valves, the shorter the wire length

## Advanced Features

- Program the corresponding station number as part of initial controller setup and installation 1-63
- The FUSION can be programmed from an Underhill Portable Programmer with updated software.
- Connects to a 2Wire path with a single pair of wires directly to the solenoid
- Ultra-low holding current allows more stations to be operated at one time if control system can be support this with programming capability
- The FUSION 2Wire Decoder-in-Solenoid comes standard with co-molded LED providing visual feedback as follows:
  - Green Color – Voltage is being sent down the 2Wire path
  - Red Color – No decoder station address or solenoid is “On” for multi-wire applications
  - Orange – Decoder has been signaled “On” as is receiving a decoded message
  - No Color – No power, broken wire or solenoid is drawing excessive current



2-Way FUSION



3-Way FUSION

## Ordering Information

TW-FC3-DBI-24	Fusion 2Wire Decoder-in-Solenoid, 3-way commercial model fits Bermad, Dorot & Irririch valves
TW- FC2-24	Fusion 2Wire Decoder-in-Solenoid, 2-way Commercial model fits, Bermad, Rain Bird, Toro/Irritrol and Hunter series valves
TW-FC2-RBA	Solenoid adapter for Rain Bird valves
TW-FC2-HA	Solenoid adapter for Hunter valves
TW-FC2-TIA	Solenoid adapter for Toro / Irritrol Valves



25782 Obrero Drive Unit C  
Mission Viejo, CA 92691  
Phone 949.305.7050 Fax: 949.305.7051  
www.underhill.us



© 2009 Underhill International Corporation. All original equipment manufacturers, names and products presented in this publication are used for identification purposes only, and we are in no way implying that any of our products are original equipment parts. Hunter® is a registered trademark of Hunter Industries Incorporated. Form # LIT-MIRAGE-809

Products that work.....smart.™