Mirage Sleeve Valve
Specifying Information

Mirage Sleeve Valves and Accessories

Model Number	Dimensions	Description
CV-3-F-WS	20” x 20” x 10”	3” sleeve valve w/ wafer inlet/outlets and bolt kit. Manual On/Off selector, 24 VAC actuated solenoid
CV-3-T	20” x 20” x 10”	3” sleeve valve w/ female NPT inlet/outlet threads. Manual On/Off selector, 24 VAC actuated solenoid
CV-3-V-WS	20” x 20” x 10”	3” sleeve valve w/ Victaulic inlet/outlets. Manual On/Off selector, 24 VAC actuated solenoid
Sleeve Valve Accessories		
CV-SOL	2” x 4”	24 VAC actuated solenoid
CV-SOL-B	4” x 4”	Solenoid base only (solenoid not included) for all sleeve valve models
FA-3S80	20” x 2”	Sch 80 PVC flange adapter w/ 4- hole bolt pattern (loose ring flange x slip)
FA-3DI	20” x 2”	3” ductile iron flange adapter w/ 4-hole bolt pattern (flange x bell)

Mirage Stainless Steel Sprinkler Box Series





Model Number	Dimensions	Description
MSSB-IV300-1830 (stainless steel sprinkler box for 3” sleeve valve and 3” isolation valve in one box)	18” w x 30” l x 18” d w/ 2 (qty) “mouse-holes” & cover plates	2 (qty) solid lids unless specified differently
MSSB-IV300-0600 (6” tall stainless steel extensions for cold-weather climates and deeper mainlines)	Optional 6” extensions made in pairs exclusive to model above	Not applicable
MSSB-IV300 (stainless steel sprinkler box for 3” sleeve valves when no isolation valve is specified)	18” w x 18” l x 18” d w/ 2 (qty) opposing “mouse-holes” & cover plates	Solid lid (no thru-hole) made for isolation valves for either M-125’s or M-115 series

Mirage HDPE Sprinkler Box Series

Model Number	Dimensions	Description
MHDB-IV300 (HDPE sprinkler box for 3” sleeve valves when no isolation valve is specified)	18” w x 18” l x 18” d w? HPDE “side-nailers”	Solid lid (no thru-hole) made for isolation valves