

Tracker™2

Portable Irrigation Machine

The Tracker² offers a very economical solution for supplementing seasonal watering needs of ¼ to 2-acre areas. It is also ideal for irrigating athletic fields, cemeteries, polo grounds, golf course roughs, horse paddocks or other larger areas where underground irrigation is impractical. Built to last with precision German engineering and high-quality materials, this portable powerhouse can irrigate an entire football field in two passes.

The Tracker² requires a minimum of labor to operate. Comes fully assembled with the exception of a part-circle impact sprinkler included with each unit. Powered by water, it pulls itself along on a galvanized pull cable dragging up to 328 feet (100m) of 1" (minimum hose size), sold separately. Hoses can also be provided by Underhill from a wide variety of models, standard or custom lengths. Each pass irrigates about 2/3's of an acre per 8 hours or operation.



specifications

- Weight: 58 lbs. (26.3kg)
- Size: 33" | x 22" w x 22" h (965.2 | x 558.8 w x558.8 h)
- Materials: Aluminum, Brass and ABS
- Minimum Operating Water Pressure: 50 Psi, (39 bars) at the inlet connection to the Tracker²⁾
- Maximum Operating Pressure 116 Psi (8,0 bars)
- Minimum Hose Size: 1" (25.4mm)
- Radius of standard Nozzle 6.4 Nozzle, 61 feet (34 meters) @66 Psi (4,6 bars)
- Application rate: 1/8"-13/32/hr. (3-10mm/hr.)

Ordering Information

Part # T-400-2 Tracker² Portable Irrigation Machine

features

- Adjustable speed control available
- 328 ft. (100M) of pull cable (galv. Steel)
- 1/4" (6,3mm) Part circle impact sprinkler (standard)
- Automatic shut-off at 328 ft. (100m)
- Includes 1" brass quick disconnects
- Travel speed 33-82 ft/h (10-25m/h)

